

10/100/1000Mbps POE injector industrial grade max 90w POE output

## BSD-IPS9500S



### Feature

- IP40 rated Gigabit 802.3AT/BT/PoE++ Injector
- Max 90w POE output
- Network a PoE device located up to 100m (328 ft.) away
- Extreme -40 to 80 °C operating temperature range
- DC inputs with overload current protection
- Includes DIN-rail mount and wall mount



driving fiber innovation

## **Overview:**

The BSD-IPS9500S is a robust industrial Gigabit Ethernet injector compliant with 802.3at/bt (PoE++) standards and featuring an IP40 rating. Designed for extreme and rugged industrial deployments, its hardened components ensure reliability. This injector allows you to power remote PoE-enabled devices (PoE, PoE+, UPoE, or PoE++) up to 90W over a 100-meter Ethernet link from a non-PoE Gigabit switch. It includes DC power inputs with overload current protection and offers versatile mounting options with DIN-rail and wall mount brackets.

### **4-Pair PoE**

Supplies power to a PoE (up to 15.4W), PoE+ (up to 30W), or PoE++ (up to 90W) device.

### **Gigabit Ports**

The industrial PoE injector features 1 x gigabit port and 1 x gigabit PoE++ port.

### **Installation Flexibility**

A rugged IP40 rated metal enclosure with DIN-rail and wall mount brackets accommodate most installations scenarios.

### **LED Indicators**

LED indicators on the industrial PoE injector confirm PoE connectivity and Load percentage indicate.

---

**Phone:** (905) 669-6613

**Web:** [www.bsdnetworks.com](http://www.bsdnetworks.com)

**Fax:** (905) 669-6614



driving fiber innovation

Model	BSD-IPS9500S
Port	1*RJ45*10/100/1000M Data IN
	1*RJ45*10/100/1000M PoE OUT
	1* DC IN (2P) removable terminal block Grounding point
Standard	IEEE 802.3 IEEE 802.3u IEEE 802.3ab IEEE 802.3af IEEE 802.3at IEEE 802.3bt
DC IN	DC48-57V MAX 2A
Boost efficiency	/
PoE Output	DC37-57V 1.73A
Poe Out Watt	MAX 90W
Data Pin	12345678
PoE Out	1245+ 3678-
Transmission	10Base-T: two pairs of Cat3 or latter UTP/STP(≤250m) 100Base-TX: two pairs of Cat5 or latter UTP/STP(≤150m) 1000Base-T: for pairs of Cat5e or latter UTP/STP(≤100m)
Features	Plug and play without more configuration management Under-voltage, over-voltage, Over-current and short circuit protection

Phone: (905) 669-6613

Web: [www.bsdnetworks.com](http://www.bsdnetworks.com)

Fax: (905) 669-6614



driving fiber innovation

	Reliability: MTBF>100k hours
Lightning Protection	6KV 8/20us; 6KV ESD protection
Protect grade	IP40
Operation Environment	Operation Temperature: -40°C~80°C Storage Temperature: -60°C~90°C
Operation Environment Specifications	Operation Humidity: 10%~90% RH Non coagulation Storage Humidity: 5%~90% RH Non coagulation
	Product size: 88mm*30mm*100mm (L*W*H) Weight: 0.35kg
Warranty	3 years

**Phone:** (905) 669-6613

**Web:** [www.bsdnetworks.com](http://www.bsdnetworks.com)

**Fax:** (905) 669-6614